



FRONT TOW COVER FITTING GUIDE



BAILEY AUSTRALIA
info@baileyaustralia.com.au
(03) 9308 7310

IMPORTANT: CARE INSTRUCTIONS

Please follow the listed points of care to extend the life of your front tow cover:

The front of the caravan must be kept clean prior to using the tow cover. Failure to keep clean may cause unrepairable scratches. Grit may get into the seams of your tow cover from general use. To avoid the potential of grit and dirt scratching your windows make sure you cleaned the seams of the tow cover before re-zipping and use. To clean simply use a vacuum, brush or hose to remove grit and dirt.

1. Before travelling with your front tow cover, ensure that your zips are fully zipped up and the velcro flap secured. Slight movement with the tow cover is to be expected while travelling at high speeds. However if what you experience is causing discomfort please pull over safely to inspect these zips and velcro straps. If you do experience further complications please remove the front tow cover and contact us for further assistance.

To clean your front tow cover, use only cold soapy water with no harsh chemicals. You may find some rub marks from the tow cover on your caravan once the cover is removed. Marks on the fiberglass body shell are easily polished out.

2. The Alu-Tech skirt rail that houses the track for your tow cover to slide into should be kept clean. To keep this area free & clean just spray inside the rail track with silicone spray. Application of silicone spray will assist in the ease of fitment for the tow cover as well as reducing strain on the neoprene. This should be done before you fit your cover for the first time and when you feel resistance sliding up the tracks when fitting your cover.

3. Once at your camping destination for longer stay durations, we recommend that you remove your front tow cover and fold up back into its bag. Removing your tow cover will protect it from environment effects and extend its life and appearance.

Please Note: The front flap is designed for short stay overs and stops along your journey. Prolong use of the front flap zipped down for extended periods of time may result in damage to the tow cover and/or window.

Bailey Australia
(03) 9308 7310

FITTING INSTRUCTIONS

Two person fitting is recommended



STEP 1: Remove the cover from the storage bag, unfold and hold up to the front of your caravan on either side of the van.



STEP 2: Undo the zips on either side of the tow cover (from the top down)



STEP 3: Fold the middle section down, whilst holding up both side sections



STEP 4: On one side only (whilst the other is being held upright), insert the top of the cover up the awning channel and slide up to around half way and hold.

PACKING UP INSTRUCTIONS

Two person packing up is recommended



STEP 1: Unclasp the elastic hooks on the underside of the caravan



STEP 2: Undo the zips on either side of the tow cover (from the top down)



STEP 2: Pull out cover end from the awning channel on both sides and slide both sides down together. Transfer tow cover to a clean, flat area.



STEP 4: With the front of the tow cover face down, fold the other sides inwards so they meet half way.



STEP 5: Fold one side on top of the other.



STEP 6: Fold over one third of the tow cover.



STEP 7: Then fold that section over again.



STEP 8: Pull the storage bag over the tow cover and close securely.



STEP 5: Do the same on the other side. When both sides are at half way, slide both sides the rest of the way up.



STEP 6: When both sides are completely up, tuck the end into the awning channel and zip up the middle section.



As part of your tow cover kit, you will find a number of hooks.

STEP 7: Link each hook to an elastic loop located on the bottom outer edge of your tow cover and pull each one taught, screwing the hook into place on the underside of your van. Do this for each hook and loop.



STEP 8: Once each hook and loop is secured, you are now ready to take your van on the road!